



ArmaTrac 802T

Perkins 1103 C-33 Euro 3/3,3 lt/75 HP - 55 kW
 Max. Torque: 291 Nm@1400 rpm
 Double PTO speed: 540/750 (540E) or 1000 rpm
 16 Forward - 8 reserve ZF Transmission
 40km/hr speed
 Air Condition
 Low Fuel Consumptions
 Cabin and Frame Options
 4WD Option

Engine

Trade Mark / Type	Perkins 1103 C- 33T
Cylinder Volume / No	3.3 liters / 3
Compression Ratio	18.25
Cylinder Diameter x Stroke	105 x 127 mm
Aspiration	Turbocharged
Air Filter	Dry With Prefilter
Maximum Power (ISO)	75 Hp @ 2200 rpm
Maximum Torque	291 Nm @ 1400 rpm
Engine Oil	7 liters
Fuel Tank	70 liters

TRANSMISSION

Type	ZF-T537
Synchromesh Gears	16 Forward 8 Reverse

Speed Range 2.01 - 41.5 km / hr

HYDRAULIC LIFT

Functions Draft, Position, Float and Mix Controls

Pump Capacity 38 liters/min

Lifting Force 3400 kg

BRAKES

Type Oil Bath Disc Brakes With 4+4 Discs

PTO

Type Independent

R.P.M. 540 / 540E (750) rpm

Diameter 35 mm

STANDART BALLASTS

Front Ballast 10x30 kg

Rear Ballast (Each Wheel) (3+3) 50 kg

DIMENSIONS

Length 3960 mm

Wheel Base 2180 mm

Front Track Size 1485-1900 mm

Rear Track Size 1505-1905 mm

Width 1935 mm

*Products > Field Type
Tractors > 802T*

Front Axle Height	380 mm
Swinging Bar Height	360 mm
Folded Rops Height	1900 mm
Height of Exhaust Pipe	2310 mm
Distance From Front to Axle Axis	760 mm
Height of Rops	2670 mm
Distance From Lowerlink Ends to Rear Axle Axis	1020 mm
Tractor Weight	3410 kg

STANDARD TYRE SIZE

Front Tyre Size	7.50/18
Back Tyre Size	18.4/15-30

The manufacturer, Erkunt Traktor Sanayii A. Ş. realizes continual improvement policy. Therefore, it reserves the right to modify the technical characteristics indicated above without any notice.