



Unidos en la tracción
de su siembra



Motor:

Model 9LD626 /air cooled

Manufacturing lombardini 30 hp 4WD

Number of cylinders 2 diesel

Cooling twin air extractor

Clutch:

Single dry plate with foot control

Transmission:

9-speed: 6 front and 3 reverse

1 before 1.2Km/H

2 before 2.5Km/H

3 before 3.8Km/H

4 before 6.5Km/H

5 before 13.7Km/H

6 before 20.6Km/H

1 reverse 1.6Km/H

2 reverse 3.3Km/H

3 reverse 5Km/H

Bodywork:

open hood from its hinges completely for full access to the motor

brakes:

the service and parking brakes act mechanically on rear wheels

weight:

820 kg in ordinary conditions without subsequent lasters

differential coupling:

in both trees, with provision for simultaneous fixation

operation / impulse:

4ruedas driving the same diameter

management:

central joint power steering

P.T.O.:

top position in 2 speeds backwards independent 540-879 RPM or synchronized with all right rotation

speed drive of the profile delasaø 13 / 8

bottom-back position in 2 independent speeds 540 to 879 RPM or synchronized with all speeds trawl counterclockwise rotation

wheels and tires:

Wheel number 4 for 7.5 * 16 ISO wheel diameter

caution lights:

battery unit charging parking lights
light fuel load orientation
night on the road
Trailer turn signals

elevation:

hydraulic three-point elevation
jack to lift max weight according to ISO
paco effort with the hydraulic jack handle
levantade is a touch up to 1060 kg

